# **IPC** Gansow

# **CT 30**

### **Great Productivity**



Scrubs in difficult to reach areas



Solution control (Solenoid valve)



Brush control with soft start





## **High Performance**



CFS (Center Flow System)



High quality and performance vacuum motor

Great maneuverability thanks to an optimum

weight distribution

Ergonomics, User Friendly



Easy to transport



Extractable recovery tank



Battery level indicator



#### Removable recovery tank

The recovery tank can be removed simply without tools to help the operations of dirty water drain and have an easy access to internal compartments.

Techncal data		CT30 C	CT30 B
Scrubbing width	mm	450	450
Suction width	mm	550	550
Productivity (max speed)	m²/h	1670	1670
Number of brushes		1 (disc)	1 (disc)
Solution tank capacity	I	28	28
Recovery tank capacity	I	30	30
Power supply		230V 50 Hz	24V (2x12V)
Max speed	Km/h	3,5	3,5
Weight (net)	Kg	50	50
Dimensions (LxWxH)	mm	960x550x1220	960x550x1220



#### Scrubber driers





# Low Maintenance Cost



Brush replacement without tools



Squeegee blades can be used on 4 sides before replacement



Easy access to internal compartments

#### **Robust Construction**



Tanks and surrounding body in high density polyethylene



Oil bath reduction gear box



Brush head designed to absorb harsh impact (optional)



Squeegee system designed to absorb harsh impact

**IPC** Gansow



Panel control switches protected against water and humidity



#### Easy to use control panel

The control panel, easy to use and intuitive, allows to activate the brush, the vacuum motor and water supply.





#### Height-adjustable handlebar

It is possible to adjust the handlebar height during work to ease the cleaning operations in difficult to reach areas.



